

HYDRAULIC POWER UNITS FOR SHEARING TOOLS

HC900R3 | HC1300R3

**INTERNATIONAL
DISTRIBUTION PARTNERS
WANTED**



SAFETY &
RELIABILITY



HIGH
PERFORMANCE



INDUSTRY
4.0 / 5.0



CUSTOM
SOLUTIONS



HC900R3

HC1300R3

HC900R3

Hydraulic power unit
for shearing tools

- MAX PRESSURE
140 bar
- PUMP FLOW RATE
6 / 8 / 11 cc/rev
- MOTOR POWER
2,2 / 3 / 4 kW
(depending on the version)
- ACCUMULATOR CAPACITY
0,35 / 0,5 / 0,75 L
pre-charged with N₂
- POWER SUPPLY
230 / 400V 50/60Hz
(depending on the version)
- WEIGHT (approx.)
80 kg



2

HC1300R3

Hydraulic power unit
for shearing tools

- MAX PRESSURE
180 bar
- PUMP FLOW RATE
14 / 18 / 22 cc/rev
- MOTOR POWER
2,2 / 3 / 4 kW
(depending on the version)
- PNEUMATIC / ELECTRIC
TWO-HAND SAFETY
CONTROL
- POWER SUPPLY
230 / 400V 50/60Hz
(depending on the version)
- WEIGHT (approx.)
80 kg



3

DESIGNED FOR PROFESSIONAL APPLICATIONS

USED IN SLAUGHTERING AND
MEAT PROCESSING OF:



PIG



SHEEP



POULTRY




BOVINE

STANDARD, MULTIPLE AND CUSTOM SOLUTIONS

- Standard units ready for installation
- Multiple-tool systems
with one power unit
- Custom engineered solutions
for specific requirements
- Compact, efficient
and reliable design



MULTIPLE-TOOL SYSTEMS



CUSTOM ENGINEERED SOLUTIONS

INDUSTRY 4.0 / 5.0 READY



ADVANCED SENSORS
Real-time monitoring and
predictive diagnostics



HMI TOUCH SCREEN
Intuitive operator
interface



CONNECTIVITY
Remote control and
integration

5

BECOME A DOT DISTRIBUTION PARTNER



We are expanding our
international distribution network.



We are looking for experienced
distributors operating in the
slaughtering and meat processing
industry.



Attractive partnership conditions
and full technical & commercial
support.



INTERESTED IN REPRESENTING
DOT IN YOUR MARKET?

info@dotitaly.it
www.dotitaly.it



6

